

## 小型端子 Miniature terminal blocks



**RL3E-Z**



**RL3E-Z-PE**

端子厚度 / 宽度 (mm): 5.2 / 28  
高度(TH15) (mm): 32

IEC 数据	IEC Data	刚性导线 Rigid mm <sup>2</sup>	柔性导线 Flexible mm <sup>2</sup>	AWG	I A	U V
IEC 60947-7-1	IEC 60947-7-1	0.2-4	0.2-2.5	24-12	32	400

过电压类别	Overvoltage Category	(-)	III			
额定冲击电压	Rating impulse voltage	(KV)	6			
污染等级	Pollution degree	(-)	3			
绝缘材料组别	Insulating Material Group	(-)	I			
绝缘材料	Insulating Material	(-)	PA			
材料阻燃等级 UL94	Flammability class UL94	(-)	V2			
螺钉/扭矩	Screw/Torque	(-/Nm)	M3 / 0.6-0.8			
剥线长度	Stripping length	(mm)	8			

UL 数据	UL Data		
额定电压 / 电流	Rate Voltage / Current	(V / A)	600 / 20
压线范围	Wire Range	(AWG)	28-12

配件	Accessories	型号 mode	定货号 order number
1. 端盖, 厚 1 mm	End Cover: thickness, 1 mm	G-JUT1-2.5/4E	8050151
2. 中心联络件: 用于端子中央横向桥接, 螺钉头带绝缘圈, 10 位, 可分, 带 10 枚螺钉	Middle Bridge: for cross connections in the terminal center, screw heads with insulating collar, 10 positions with screw, divisible,	JFB10-2.5	5585110
3. 侧边联络件: 全绝缘, 可分 2、3、10 位	Insertion bridge: full insulation, in 2, 3, 10 positions	JEB2、3、10-2.5	5582102、3、0
4. 跨接联络件: 10 位, 可分; 带 10 枚螺钉; 为形成跳过某些端子的跨接	Cross connection adaptor: 10 positions with screw, divisible, for switchable branches	-	-
5. 绝缘隔片: 用于相邻桥接件间的电气隔离; 可事后插入; 不占导轨的任何空间	Separating plate, for electrical separation of neighboring bridge, can be fitted later, no loss of pitch	JS-KK3	8751101
6. 分组隔板: 用于端子组间的视觉及电气隔离; 厚 2.5 mm	Partition Plate: for visual and electrical separation of terminal groups, 2.5 mm thick.	JAP-E	8750151
7. 测试插座: 与测试插头形成测试连接	Test socket: for test connection with test plug	PSB3/10/4	8753101
8. 标记条: 有横向和竖向两种字体, 10 位	Marker Strip: with horizontal and vertical word, 10 spaced	ZB5	8868102
9. 固定终端件: 有横向和竖向两种字体, 10 位	Terminal Fixed component.	E/1E	5103007