

通用试验端子 Universal Test disconnect terminal blocks



RL6T



端子厚度 / 宽度 (mm): 8.2 / 72
高度 (TH35-7.5 / TH35-15 / G32) (mm): 51.5 / 59 / 56

IEC 数据	IEC Data	刚性导线 Rigid mm ²	柔性导线 Flexible mm ²	AWG	I A	U V
IEC 60947-7-1	IEC 60947-7-1	0.5-10	0.5-6	20-8	57	400

过电压类别	Overvoltage Category	(-)	III
额定冲击电压	Rating impulse voltage	(KV)	6
污染等级	Pollution degree	(-)	3
绝缘材料组别	Insulating Material Group	(-)	I
绝缘材料	Insulating Material	(-)	PA
材料阻燃等级 UL94	Flammability class UL94	(-)	V0
接线位螺钉: 螺钉/扭矩	Terminal point: Screw/Torque	(-/Nm)	M4 / 1.2-1.5
分断滑块螺钉: 螺钉/扭矩	Disconnect slide: Screw/Torque	(-/Nm)	M3 / 0.6-0.8
剥线长度	Stripping length	(mm)	13

UL 数据	UL Data		
额定电压 / 电流	Rate Voltage / Current	(V / A)	300 / 50
压线范围	Wire Range	(AWG)	26-8

配件	Accessories	型号 mode	定货号 order number
1. 端盖, 厚 2.2 mm	End Cover: thickness, 2.2 mm	G-JUT1-6S	8050109
2. 中心联络件: 用于端子中央, 实现横向桥接, 螺钉头带绝缘圈, 可分 2、3、5、10 位。	Middle Bridge: for cross connections, screw heads with insulating collar, in 2, 3, 5, 10 positions	JEB10-6S/S(短) JEB10-6S/S(长)	5585170S 5585170L
3. 侧边联络件: 全绝缘, 可分 2、3、10 位	Insertion bridge: full insulation, in 2, 3, 10 positions	JEB2、3、10-6	5585122、3、0
4. 分组隔板: 用于端子组间的视觉及电气隔离; 0.8 mm 厚	Partition Plate: for electrical separation of neighboring bridges in terminal center, 0.8 mm thick.	JAP/6S	8750105
5. 测试插头: 与测试插座形成测试连接	Test plug: to form a testing connection by using test socket	PS	5553102
6. 标记条: 有横向和竖向两种字体, 10 位	Marker Strip: with horizontal and vertical word, 10 spaced	ZB8	8868104