

刀闸分断接线端子 Knife disconnect terminal blocks



RL5K



端子厚度 / 宽度 (mm): 6.2 / 51
高度 (TH35-7.5 / TH35-15 / G32) (mm): 47 / 54.5 / 52

IEC 数据	IEC Data	刚性导线 Rigid mm ²	柔性导线 Flexible mm ²	AWG	I A	U V
IEC 60947-7-1	IEC 60947-7-1	0.2-4	0.2-4	24-12	16	800

过电压类别	Overvoltage Category	(-)	III
额定冲击电压	Rating impulse voltage	(KV)	8
污染等级	Pollution degree	(-)	3
绝缘材料组别	Insulating Material Group	(-)	I
绝缘材料	Insulating Material	(-)	PA
材料阻燃等级 UL94	Flammability class UL94	(-)	V2
螺钉 / 扭矩	Screw/Torque	(-/Nm)	M3 / 0.6-0.8
剥线长度	Stripping length	(mm)	8

UL 数据	UL Data		
额定电压 / 电流	Rate Voltage / Current	(V / A)	600 / 15
压线范围	Wire Range	(AWG)	30-10

配件	Accessories	型号 mode	定货号 order number
1. 端盖, 厚 1.5 mm	End Cover: thickness, 1.5 mm		
2. 中心联络件: 用于端子中央, 实现横向桥接, 螺钉头带绝缘圈, 可分 2、3、5、10 位。	Middle Bridge: for cross connections, screw heads with insulating collar, in 2, 3, 5, 10 positions	-	-
3. 侧边联络件: 全绝缘, 可分 2、3、10 位	Insertion bridge: full insulation, in 2, 3, 10 positions	JEB2、3、10-4	5585112、3、0
4. 测试插头: 与测试插座形成测试连接	Test plug: to form a testing connection by using test socket	MPS	5553101
5. 标记条: 有横向和竖向两种字体, 10 位	Marker Strip: with horizontal and vertical word, 10 spaced	ZB6	8868103