

## 保险丝接线端子 Fuse terminal blocks



### RL5F



端子厚度 / 宽度 (mm): 8.2 / 72.5  
高度 (TH35-7.5 / TH35-15 / G32) (mm): 56.5 / 64 / 61.5

适用于 G 型保险丝，规格为 5 x 20, 5 x 25, 5 x 30 mm 的保险丝

	发光二极管显示:电压 [V AC/DC]	电流 [mA]	型号	定货号
带发光显示	15 - 30	3.5-8.1	RL5F/LED24	5574134
带发光显示	110 - 250	0.5-1.0	RL5F/LA250	5574135

IEC 数据	IEC Data	刚性导线 Rigid mm <sup>2</sup>	柔性导线 Flexible mm <sup>2</sup>	AWG	I A	U V
IEC 60947-7-1	IEC 60947-7-1	0.2-6	0.2-4	24-10	32	630

过电压类别	Overvoltage Category	(-)	III
额定冲击电压	Rating impulse voltage	(KV)	8
污染等级	Pollution degree	(-)	3
绝缘材料组别	Insulating Material Group	(-)	I
绝缘材料	Insulating Material	(-)	PA
材料阻燃等级 UL94	Flammability class UL94	(-)	V2
螺钉 / 扭矩	Screw/Torque	(-Nm)	M3 / 0.6-0.8
剥线长度	Stripping length	(mm)	8

UL 数据	UL Data		
额定电压 / 电流	Rate Voltage / Current	(V / A)	300 / 30
压线范围	Wire Range	(AWG)	30-10

配件	Accessories	型号 mode	定货号 order number
1. 侧边联络件:全绝缘,插入压线框中,并卡在端子的绝缘外壳上	Insertion bridge: full insulation, is laid into terminal sleeve and snap fitted into the terminal housing	JEB2、3、10-6	5585182、3、0
2. 标记条:有横向和竖向两种字体,10位	Marker Strip: with horizontal and vertical word, 10 spaced	ZB8	8868104