

双层接线端子 Double-level terminal blocks



RL3D-2



RL3D-2L



端子厚度 / 宽度 (mm): 5.2 / 56
高度(TH35-7.5 / TH35-15 / G32) (mm): 62 / 69.5 / 67

IEC 数据	IEC Data	刚性导线 Rigid mm ²	柔性导线 Flexible mm ²	AWG	I A	U V
IEC 60947-7-1	IEC 60947-7-1	0.2-4	0.2-2.5	24-12	32	500
过电压类别	Overvoltage Category	(-)	III			
额定冲击电压	Rating impulse voltage	(KV)	6			
污染等级	Pollution degree	(-)	3			
绝缘材料组别	Insulating Material Group	(-)	I			
绝缘材料	Insulating Material	(-)	PA			
材料阻燃等级 UL94	Flammability class UL94	(-)	V0			
螺钉 / 扭矩	Screw/Torque	(-/Nm)	M6 / 0.6-0.8			
剥线长度	Stripping length	(mm)	8			

UL 数据	UL Data		
额定电压 / 电流	Rate Voltage / Current	(V / A)	600 / 20
压线范围	Wire Range	(AWG)	28-12

配件	Accessories	型号 mode	定货号 order number
1. 端盖, 厚 2.5 mm	End Cover: thickness 2.5 mm	G-JUT1-2.5/4	8050104
2. 中心联络件: 用于端子中央, 实现横向桥接, 螺钉头带绝缘圈, 桥接前需将外壳的隔片打通	Middle Bridge: for cross connections, screw heads with insulating collar, first remove partition plate	JFBN10-2.5	5585180
3. 侧边联络件: 全绝缘, 插入压线框中, 并卡在端子的绝缘外壳上	Insertion bridge: full insulation, is laid into terminal sleeve and snap fitted into the terminal housing	JEB2、3、 10-2.5	5582102、3、0
4. 跨接联络件: 10 位带10 枚螺钉, 可分; 为形成跳过某些端子的跨接	Cross connection adaptor: in 10 digit with 10 screw, detachable, for switchable branches	JB10-2.5	5584101
5. 绝缘隔片: 用于相邻联络件间的电气隔离; 可事后插入; 不占导轨的任何空间	Separating Disk: for electrical separation of neighboring adaptors; can be fitted later, no loss of pitch cross section.	JS-KK3	8751101
6. 补偿端板: 与普通端子相邻排列时, 用来抵消层间错位; 厚 2.5mm	Space Cover: compensates for level offset if standard TB are to be fitted adjacently, 2.5m thick	DG-JUT1-2.5/4	8053101
7. 补偿端板: 与普通端子相邻排列时, 用来抵消层间错位; 厚 2.5mm	Space plate: compensates for level offset if standard TB are to be fitted adjacently, 2.5m thick	DP-JUT1-2.5/4	8053102
8. 标记条: 有横向和竖向两种字体, 10 位	Marker Strip: with horizontal and vertical word , 10 spaced	ZB5	8868102
9. 警示牌	Warning board	JWS5	8867110