

## 通用组合接线端子 DIN Rail terminal blocks



### RL1.5



端子厚度 / 宽度 (mm): 4.2 / 42.5  
高度 (TH35-7.5 / TH35-15 / G32) (mm): 42 / 49.5 / 47

IEC 数据	IEC Data	刚性导线 mm <sup>2</sup>	柔性导线 mm <sup>2</sup>	AWG	I A	U V
IEC 60947-7-1	IEC 60947-7-1	0.14-1.5	0.14-1.5	26-16	17.5	500

过电压类别	Overvoltage Category	(-)	III
额定冲击电压	Rating impulse voltage	(KV)	6
污染等级	Pollution degree	(-)	3
绝缘材料组别	Insulating Material Group	(-)	I
绝缘材料	Insulating Material	(-)	PA
材料阻燃等级 UL94	Flammability class UL94	(-)	V0
螺钉 / 扭矩	Screw/Torque	(-Nm)	M2 / 0.22-0.25
剥线长度	Stripping length	(mm)	7

UL 数据	UL Data		
额定电压 / 电流	Rate Voltage / Current	(V / A)	300 / 15
压线范围	Wire Range	(AWG)	30-14

配件	Accessories	型号 mode	定货号 order number
1. 端盖, 厚 1.5 mm	End Cover: thickness 1.5 mm	G-JUT1-1.5/2.5B	8050101
2. 中心联络件: 用于端子中央, 实现横向桥接, 螺钉头带绝缘圈, 10 位, 可分带 10 枚螺钉	Middle Bridge: for cross connections in the terminal center, screw heads with insulating collar, 10 positions with screw, divisible	JFBN10-1.5	5585100
3. 侧边联络件: 全绝缘, 2 位、3 位、10 位	Insertion bridge: full insulation in 2,3,10 digit	-	-
4. 跨接联络件: 10 位带 10 枚螺钉, 可分; 为形成跳过某些端子的跨接	Cross connection adaptor: 10 positions with screw, divisible, for switchable branches	-	-
5. 绝缘隔片: 用于相邻联络件间的电气隔离; 可事后插入; 不占导轨的任何空间	Separating Disk: for electrical separation of neighboring adaptors; can be fitted later, no loss of pitch cross section.	-	-
6. 分组隔板: 用于端子组间的视觉及电气隔离; 厚 1.5 mm	Partition Plate: for visual and electric separation between neighboring terminal groups	JAP	8750101
7. 测试插座: 与测试插头形成测试连接	Test socket: to form a testing connection by using test plug	-	-
8. 测试插头: 与测试插座形成测试连接	Test plug: to form a testing connection by using test socket	-	-
9. 标记条: 有横向和竖向两种字体, 10 位	Marker Strip: with horizontal and vertical word, 10 spaced	ZB4	8868101
10. 标记卡	Mark clip	KLM-A	5574143
11. 终端固定件	Terminal fixed component	E/1	5103001
12. 警示牌	Warning board	-	-