


欧式 PCB 板接线端子 Euro for PCB terminal blocks



EL5HT

Pitch: 9.52 mm



技术数据

IEC 数据	刚性	柔性	I	U
	导线	导线		
	mm ²	mm ²	A	V

连接数据	0.2-6	0.2-4	32	690
绝缘材料组别			I	
过电压类别		III	III	II
污染等级		3	2	2
额定电压(V)		690	1000	1000
额定冲击电压(KV)			8	
绝缘材料/阻燃等级		PA / UL94 V0		
螺钉/扭矩(-Nm)		M3 / 0.5-0.6		
剥线长度(mm)		8		
引脚尺寸(mm)		0.8x1.0		
线路板孔径(mm)		Φ1.3		

UL 数据

额定电压/电流(V/A)	300 / 10
压线范围(AWG)	30-10

Technical Data

IEC Data	Rigid	Flexible	I	U
	Solid	stranded		
	mm ²	mm ²	A	V

Connection data	0.2-6	0.2-4	32	690
Insulating Material Group			I	
Overvoltage Category		III	III	II
Pollution degree		3	2	2
Rate Voltage(V)		690	1000	1000
Rate impulse Voltage(KV)			8	
Insu. Material / Inflamm. class		PA / UL94 V0		
Screw/Torque(-Nm)		M3 / 0.5-0.6		
Stripping length(mm)		8		
Terminal Dimension(mm)		0.8x1.0		
PCB Hole diameter(mm)		Φ1.3		

UL Data

Rate Voltage/Current(V/A)	300 / 10
Wire Range(AWG)	30-10

定货型号 How to Order No.

位数 No. of Positons	间距 pitch: 9.52mm
2	EL5HT-02-9.52
3	EL5HT-03-9.52

说明：以上为标准颜色：GN=Green 绿色，省略。

可拼接最长位数不超过 24 位。