

通用型接地接线端子 Universal ground terminal blocks



RL1.5-PE



端子厚度 / 宽度 (mm): 4.2 / 42.5
高度 (TH35-7.5 / TH35-15 / G32) (mm): 42 / 49.5 / 47

IEC 数据	IEC Data	刚性导线 Rigid mm ²	柔性导线 Flexible mm ²	AWG kcmil	I A	U V
IEC 60947-7-1	IEC 60947-7-1	0.14-1.5	0.14-1.5	26-16	-	-

过电压类别	Overvoltage Category	(-)	III
额定冲击电压	Rating impulse voltage	(KV)	6
污染等级	Pollution degree	(-)	3
绝缘材料组别	Insulating Material Group	(-)	I
绝缘材料	Insulating Material	(-)	PA
材料阻燃等级 UL94	Flammability class UL94	(-)	V0
接线位 螺钉 / 扭矩	Terminal point Screw/Torque	(-Nm)	M2 / 0.22-0.25
中央紧固 螺钉 / 扭矩	Fastening Screw/Torque	(-Nm)	M2 / 0.22-0.25
剥线长度	Stripping length	(mm)	7

UL 数据	UL Data		
额定电压 / 电流	Rate Voltage / Current	(V / A)	- / -
压线范围	Wire Range	(AWG)	30-14

配件	Accessories	型号 mode	定货号 order number
1 侧边联络件:全绝缘,2、3、10 位	Insertion bridge: full insulation, in 2, 3, 10 positions		
2. 标记条:有横向和竖向两种字体,10 位	Marker Strip: with horizontal and vertical word, 10 spaced	ZB4	8868101